

METAL PROTECTING TUBES

Ordering Code	T/C Gauge	"M" I.D.	"V"	"S" Nominal Wall	"N" T/C Connection
MT-18	20	.269"	.405"	.068"	1/8" NPT
MT-14	14	.364"	.540"	.088"	1/4" NPT
MT-12	8	.622"	.840"	.109"	1/2" NPT
MT-34	8	.824"	1.050"	.113"	3/4" NPT
MT-10	8	1.049"	1.315"	.133"	1" NPT

Ordering Code	T/C Gauge	"M" I.D.	"V"	"S" Nominal Wall	"N" T/C Connection	"P" Process Connection
MTP-18	20	.269"	.405"	.068"	1/8" NPT	1/4" NPT
MTP-14	14	.364"	.540"	.088"	1/4" NPT	1/2" NPT
MTP-12	8	.622"	.840"	.109"	1/2" NPT	3/4" NPT
MTP-34	8	.824"	1.050"	.113"	3/4" NPT	1" NPT
MTP-10	8	1.049"	1.315"	.133"	1" NPT	1 1/4" NPT

Other process connections available upon request

Standard length "B" is 3", unless otherwise specified

Ordering Code	T/C Gauge	"M" I.D.	"V"	"S" Nominal Wall	"N" T/C Connection
MTF-18	20	.269"	.405"	.068"	1/8" NPT
MTF-14	14	.364"	.540"	.088"	1/4" NPT
MTF-12	8	.622"	.840"	.109"	1/2" NPT
MTF-34	8	.824"	1.050"	.113"	3/4" NPT
MTF-10	8	1.049"	1.315"	.133"	1" NPT

Standard length "B" is 3", unless otherwise specified.

ORDERING INFORMATION:

1. Catalog number from first column.
2. Overall length of protecting tube.
3. Length below process connection.
4. Pressure rating and facing of flange.
5. Material of construction. (Bushings and flanges are steel unless otherwise specified.)

REMARKS:

1. Standard Materials are 304SS, 316SS, 347SS, 446SS, Inconel, and Steel. Other materials are available on special order.
2. Standard Lengths for "A" are 12", 15", 18", 24", 30", 36" and 48". Other lengths are available on special order.
3. Pipe Schedule - Schedule 40 pipe is regularly used. Schedule 80 or 160 pipe is available on special order.
4. Open End protecting tubes are available for so specifying.

